



**RACCORDS À
SERTIR**



TABLEAU DE SERTISSAGE

Type de flexible	Diam. Intérieur		Ø ext. (mm)	Diam. Ext. Jupe	Nombre de tresses	Dénuder		Type de jupe	Sertir jusque diam. Ext. jupe
	pouce	mm				Int.	Ext.		
GH 781 2 tresses - caoutchouc suivant norme: EN 857/2SC.									
AQ-HSK6	1/4"	6	13,5	22,4	2				16,9
AQ-HSK8	5/16"	8	15,0	24,6	2				18,0
AQ-HSK10	3/8"	10	17,4	27,1	2				20,7
AQ-HSK13	1/2"	13	20,5	31,0	2				24,7
AQ-HSK16	5/8"	16	23,7	35,2	2				28,3
AQ-HSK20	3/4"	20	27,4	39,7	2				31,6
AQ-HSK25	1"	25	35,6	49,3	2				39,8
GH793 2 tresses - caoutchouc suivant norme: EN 853-2SN									
AQ-HST6	1/4"	6	15,0	22,4	2				17,3
AQ-HST8	5/16"	8	16,6	24,6	2				19,0
AQ-HST10	3/8"	10	19,0	27,1	2				21,2
AQ-HST13	1/2"	13	22,2	31,0	2				25,1
AQ-HST16	5/8"	16	25,4	35,2	2				28,7
AQ-HST20	3/4"	20	29,3	39,7	2				32,5
AQ-HST25	1"	25	38,1	49,3	2				41,4
2755 4 tresses - caoutchouc suivant norme: EN 856 (4SP)									
AQ-HDR10	3/8"	10	21,4	25,0	4		22,9	AQ-SF4S10	20,8
AQ-HDR13	1/2"	13	24,6	28,0	4		27,9	AQ-SF4S13	24,0
AQ-HDR16	5/8"	16	28,2	32,0	4		30,0	AQ-SF4S16	28,5
AQ-HDR20	3/4"	20	32,2	36,0	4		30,5	AQ-SF4S20	32,1
AQ-HDR25	1"	25	39,7	44,0	4		34,5	AQ-SF4S25	38,9
GH506 4 tresses - caoutchouc suivant norme: EN 856 (4SH)									
AQ-4SH20	3/4"	20	32,3	43,1	4	10,0	36,2	AQ-SF4H20-1W	37,1
AQ-4SH25	1"	25	38,4	48,8	4	13,5	47,0	AQ-SF4H25-1W	43,5
AQ-4SH32	1 1/4"	32	45,5	57,2	4	14,0	56,5	AQ-SF4H32-1W	50,5

